

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
**WO 2004/000661 A2**

(51) International Patent Classification<sup>7</sup>: **B65D**  
(21) International Application Number:  
PCT/US2003/020264  
(22) International Filing Date: 25 June 2003 (25.06.2003)  
(25) Filing Language: English  
(26) Publication Language: English  
(30) Priority Data:  
60/391,349 25 June 2002 (25.06.2002) US

(71) Applicant (for all designated States except US): **STULL TECHNOLOGIES** [US/US]; 17 Veronica Avenue, Somerset, NJ 08873 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **STULL, Gene** [US/US]; 1 Winston Farm Lane, Far Hills, NJ 07931 (US). **AUER, Robert** [US/US]; 546 Pen Estates, East Stroudsburg, PA 18301 (US).

(74) Agents: **HELFGOTT, Samson et al.**; Katten, Muchin, Zavis, Rosenman, 575 Madison Avenue, New York, NY 10022-2585 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TAMPER-EVIDENT QUICK TWIST CLOSURE



(57) Abstract: A cap with a tamper-evident ring is designed to snap engage a container neck that is provided with an upper and lower bead. A ring of teeth provided along an inside skirt of the cap engage teeth located along an inside wall of the container neck. When the cap is snapped onto the container neck, both sets of teeth automatically engage and a plug seal provided on the cap engages the container upper bead. By turning the cap clockwise or counterclockwise, the side angles of the teeth force the cap to disengage upwards over the upper bead and unsnap from the container neck. When the closure is opened for the first time, the ring breaks away from the cap and slides down the container neck below the lower bead, which keeps the ring from coming off the container and provides evidence that the cap had been opened.

WO 2004/000661 A2